

Model AC68

Clamp Type Digital Multimeter



- Top-of-the-line professional clamp DMM
- 8 functions/11 ranges
- AC and DC
- Data and AC Peak Hold
- DC auto zero
- 4000-count
- Carrying case included
- CAT II 600 V, CAT III 300 V rated

AC68 Specifications (at 23°C ± 5 °C; < 80 % R.H. non-condensing)

DC Voltage	
Ranges	600 V
Accuracy	± (0.75 % rdg + 2 dgts)
Resolution	1 V in 600 V range
Input Impedance	10 MΩ
AC Voltage (40-450 Hz)	
Range	400 V, 600 V
Accuracy	± (1.2 % rdg + 5 dgts)
Resolution	0.1 V in 400 V range
Input Impedance	10 MΩ
DC Current	
Ranges	400 A, 600 A
Accuracy	± (2 % rdg + 5 dgts)
Resolution	0.1 A in 400 A range
AC Current (40-450 Hz)	
Ranges	400 A, 600 A
Accuracy	± (2 % rdg + 5 dgts)
Resolution	0.1 A in 400 A range
Frequency (Hz), Current and Voltage	
Ranges	4 kHz, 20 kHz
Accuracy	± (0.5 % rdg + 5 dgts)
Resolution	1 Hz in 4 kHz range
Sensitivity	5 A/1 V in 4 kHz range 5 A/5 V in 20 kHz range
Resistance	
Range	4 kΩ
Accuracy	± (1.0 % rdg + 5 dgts)
Resolution	1 Ω in 4 kΩ range
Open Circuit Volts	0.5 V DC
Max Short Circuit Current	0.8 mA
Diode Test	
Accuracy	± (1.0 % rdg + 2 dgts)
Resolution	0.001 V
Open Circuit Volts	3.2 V DC
Max Short Circuit Current	0.8 mA
Continuity	
Range Threshold	Tone at 40 Ω ± 15 Ω
Open Circuit Volts	3.2 V DC
Max Short Circuit Current	0.8 mA
Peak Hold Measurement AC Voltage (40-450 Hz)	
Range	400 V, 600 V
Accuracy	± (1.5 % rdg + 10 dgts)
Resolution	0.1 V in 400 V range
Input Impedance	10 MΩ
Peak Hold Measurement AC Current (40-450 Hz)	
Range	400 A, 600 A
Accuracy	± (2.0 % rdg + 10 dgts)
Resolution	0.1 A in 400 A range
Overload Protection	
Voltage	1000 V DC/750 V AC
Current	800 Amps
Resistance	660 V rms
Diode	660 V rms

Model AC68

Clamp Type Digital Multimeter

General Specifications

Display: 3¾ digit, LCD, max reading of 3999; **Display Update Rate:** 2/sec, nominal; **Power:** 9 V battery (NEDA 1604, IEC 6F22); **Battery Life:** 200 hours (Alkaline); **Operating Temperature:** 0 °C to + 40 °C < 80 % R.H.; **Storage Temperature:** - 10 °C to + 60 °C, < 70 % R.H. non-condensing; **Maximum Jaw Opening:** 40 mm (1.57"); **Dimensions (WxHxD):** 76 x 228 x 39 mm (3" x 9" x 1.5"); **Weight (incl. Battery):** 465 grams; **Included Accessories:** Test Leads, battery, manual and carrying case

Features

DC Current (Zero adjustment button); **Ranging:** Manual function and range selection with rotary selector switch; **Autoranging** for frequency measurement; **Data Hold:** Holds the display reading for all functions and ranges; **Peak Hold:** Converts and displays the peak value for AC Volts and amps readings; **Low Battery Indication;** **Auto-Power Off** after 30 minutes; **Warranty:** One-year

Optional Accessories

DL243C Basic Test Lead Kit; **DL248C** Deluxe Test Lead Kit; **TL35A** Test Lead Set with Alligator Clips

For additional accessories, see the Accessories Compatibility Guide at www.metermantesttools.com



Meterman.
The right tool for the job.™

Meterman Test Tools
website: www.metermantesttools.com
email: info@metermantesttools.com
6920 Seaway Blvd.
Everett, WA 98203
fax: 425-446-4882
tel: 877-596-2680

Meterman Test Tools Europe
P.O. Box 1186
5602 BD Eindhoven
The Netherlands

©2002 Meterman Test Tools. All rights reserved.
1/2002 1646618 D-ENG-N Rev A Pub_ID 10516-eng Rev. 1



S J ELECTRONICS
POWER • TEST & MEASUREMENT

0800 583 44 55

Tel: +44 1536 416 200

Fax: 0800 583 55 66

sales@sjelectronics.co.uk

www.sjelectronics.co.uk