

Model AD40A

Digital Ammeter



AD40A Specifications (at 23°C±5°C, <80% R.H. non-condensing)

AC Current	
Ranges	40 A, 400 A
Accuracy	± (2 % rdg + 10 dgts)
Resolution	0.01 A in 40 A range
Overload Protection	
	660 A for AC current



General Specifications

Display: 3¼ digit LCD (max reading 3999); **Overrange Indication:** "OL" indicated; **Low Battery Indication:** Battery symbol; **Power Supply:** Two (2) 1.5 V AAA batteries (UM-4); **Battery Life:** Alkaline 300 hours, approx.; **Maximum Jaw Opening:** 25.4 mm; **Dimensions (WxHxD):** 64 x 190 x 36 mm; **Weight:** 250 g (incl. Battery); **Operating Temperature:** 0 °C to + 40 °C, < 80 % R.H. non-condensing; **Storage Temperature:** -10 °C to + 60 °C, < 70 % R.H. non-condensing, batteries removed; **Included Accessories:** Manual, carrying case

Features

Auto Power Off: Approx. 30 minutes after no function change; **42 segment Bargraph;** **Data Hold;** **Warranty:** One-year



- Low-cost, miniature digital ammeter
- 400 A AC range
- 4000-count display with bargraph
- Autoranging
- Data Hold
- Auto-off
- CAT III 600 V rated

Model AD40A

Digital Ammeter

Meterman.
The right tool for the job.[™]

Meterman Test Tools
website: www.metermantesttools.com
email: info@metermantesttools.com

6920 Seaway Blvd.
Everett, WA 98203
fax: 425-446-4882
tel: 877-596-2680

Meterman Test Tools Europe
P.O. Box 1186
5602 BD Eindhoven
The Netherlands

©2002 Meterman Test Tools. All rights reserved.
1/2002 1646259 D-ENG-N Rev A Pub_ID 10511-eng Rev. 1



S J ELECTRONICS
POWER • TEST & MEASUREMENT

0800 583 44 55

Tel: +44 1536 416 200

Fax: 0800 583 55 66

sales@sjelectronics.co.uk

www.sjelectronics.co.uk