

## 350 Series AC/DC Clamp Meters





New

Fluke 355

COM V













### **Included Accessories**

Fluke 353: C43 Soft Meter Case, 6 AA batteries, users manual Fluke 355: C43 Soft Meter Case, 6 AA batteries, TL224 SureGrip\* Silicone Test Lead Set, TP2 Slim Reach Test Probe Set (2 mm), AC285 SureGrip\* Alligator Clip Set, users manual

### Ordering information

Fluke 353 AC/DC Clamp Meter Fluke 355 AC/DC Clamp Meter

# True-RMS, 2000 A Clamp Meters for industrial and utility applications

Confidently take reliable readings with the true-rms, Fluke 353/355 Clamp Meters; the tools of choice for high current measurement up to 2000 A. The extra-wide jaw easily clamps around large conductors, typically found in high current applications. The rugged design and CAT IV 600 V, CAT III 1000 V ratings add an extra element of protection when taking high-powered measurements.

Accurate peak measurements can be taken using the in-rush current mode – ideal for motors and inductive loads. The 355 also measures voltage and resistance, making this the most versatile tool for utilities, electrical contractors and industrial service technicians.

### **Features**

	353	355
True-RMS measurements	•	•
Display backlight	•	•
Motor start-up current	•	•
Min/Max/Average	•	•
Voltage AC/DC		•
Resistance measurement		•
Continuity measurement with beeper		•

### **Specifications**

(Check the Fluke web for detailed specifications)

Functions	Range	353	355
Current AC/DC	0-40.00 A	1.5% ± 15 counts	1.5% ± 15 counts
	0-400.0 A	1.5% ± 5 counts	1.5% ± 5 counts
	0-2000 A; 1400 AC rms		
Crest Factor		2.4	2.4
Voltage AC/DC	0-4.000 V		1% ± 10 counts
	0-40.00 V		
	0-400.0 V		1% ± 5 counts
	0-600 V AC rms		
	0-1000 V DC		
Resistance	sistance 0-400.0 Ω		
	0-4.000 kΩ		
	0-40.00 kΩ		1.5% ± 5 counts
	0-400.0 kΩ		
Continuity beeper	Appr. ≤ 30 Ω		
Frequency	5.0Hz to 100.0Hz		0.2% ± 2 counts
	100.1Hz to 999Hz		0.5% ± 5 counts

Power Supply: 6 x 1.5V AA NEDA 15A or IEC LR6


Battery Life: 100 hours (with typical usage, backlight off)

Size (HxWxD): 300 mm x 98 mm x 52 mm

Jaw opening: 58 mm Weight: 0.814 kg Two year warranty

### **Recommended Accessories**





Tel: +44 1536 416 200 Fax: 0800 583 55 66 sales@sjelectronics.co.uk www.sjelectronics.co.uk





TL223 (Fluke 355)

L215 (Fluke 355)