

37XR

True RMS digital multimeter with component and logic test for troubleshooting electronics at the bench or on the job site.



- Inductance to 40 H, frequency to 40 MHz, capacitance to 400 μ F, logic to 20 MHz
- Input warning tone when test leads are in wrong jack
- 10,000 count, 0.1 % accuracy
- 1000 V/750 V dc/ac True RMS
- 10 Amps ac/dc, fully safety fused
- Resistance to 40 M Ω
- Continuity beeper
- Min/Max, Average, Relative, Peak, and Data Hold
- Auto power off to save battery life
- Separate door for easy battery and fuse access
- Magne-Grip™ Holster with magnetic hanging strap
- CAT III 600 V, CAT II 1000 V rated
- UL (cULus) listed
- Three-year warranty

37XR Specifications (at 23 °C \pm 5 °C, <75 % R.H. non-condensing)

DC Voltage	
Ranges	1000 mV, 10 V, 100 V, 1000 V
Accuracy	all ranges \pm (0.1 % rdg + 5 dgt)
Resolution	100 μ V
AC Voltage (45 Hz to 2 kHz) True RMS	
Ranges	1000 mV, 10 V, 100 V, 750 V
Accuracy	750 V range: 45 to 1 kHz: \pm (2.0 % rdg + 10 dgts) All other ranges, 45 to 500 Hz: \pm (1.2 % rdg + 10 dgts) All other ranges, 500 to 2 kHz: \pm (2.0 % rdg + 10 dgts)
Resolution	100 μ V
AC coupled True RMS specified from 5 % to 100 % of range	
DC Current	
Ranges	100 μ A, 1000 μ A, 10 mA, 100 mA, 400 mA, 10 A
Accuracy	100 μ A range: \pm (0.5 % rdg + 10 dgt) 1000 μ A to 400 mA ranges: \pm (0.5 % rdg + 5 dgts) 10 A range: \pm (1.5 % rdg + 10 dgt)
Resolution	0.01 μ A
AC Current (45 Hz to 1 kHz) True RMS	
Ranges	100 μ A, 1000 μ A, 10 mA, 100 mA, 400 mA, 10 A
Accuracy	100 μ A to 100 mA ranges: \pm (1.5 % rdg + 10 dgts) 400 mA range: \pm (2.0 % rdg + 10 dgts) 10 A range: \pm (2.5 % rdg + 10 dgts)
Resolution	0.01 μ A
AC coupled True RMS specified from 5 % to 100 % of range	
Resistance	
Ranges	1000 Ω , 10 k Ω , 100 k Ω , 1000 k Ω , 10 M Ω , 40 M Ω
Accuracy	1000 Ω to 1000 k Ω ranges: \pm (0.5 % rdg + 8 dgts) 10 M Ω range: \pm (1.0 % rdg + 10 dgts) 40 M Ω range: \pm (2.0 % rdg + 10 dgts)
Capacitance	
Ranges	40 nF, 400 nF, 4 μ F, 40 μ F, 400 μ F
Accuracy	40 nF, 400 μ F ranges: \pm (3.0 % rdg + 10 dgts) 400 nF to 40 μ F ranges: \pm (3.0 % rdg + 5 dgts)
Resolution	0.01 nF
Inductance	
Ranges	4 mH, 40 mH, 400 mH, 4 H, 40 H
Accuracy	(for values of Q \leq 7): \pm (5.0 % rdg + 30 dgts)
Resolution	1 μ H
Frequency	
Ranges	100 Hz, 1000 Hz, 10 kHz, 100 kHz, 1000 kHz, 10 MHz
Accuracy	all ranges: \pm (0.1 % rdg + 5 dgts)
Resolution	0.01 Hz
Duty Cycle	
Ranges	0 to 90 %
Accuracy	5V logic: \pm (2.0 % rdg + 20 dgts)
Resolution	0.01 %
Frequency Range	0 % to 10 %: 40 Hz to 990 kHz 10 % to 90 %: 40 Hz to 20 kHz
Logic Test	
Logic Type	TTL, CMOS
Thresholds	Logic 1 (Hi): TTL 2.8 V \pm 0.8 V, CMOS 4 V \pm 1 V Logic 0 (Lo): TTL 0.8 V \pm 0.5 V, CMOS 2 V \pm 0.5 V
Frequency Response	20 MHz

37XR

True RMS digital multimeter with component and logic test for troubleshooting electronics at the bench or on the job site.

37XR Specifications (at 23 °C ± 5 °C, <75 % R.H. non-condensing)

dBm	
Ranges	-13 dBm to + 50 dBm
Accuracy	45 Hz to 5 kHz: ± (0.7 dB + 8 dgts)
	5 kHz to 10 kHz: ± (2.5 dB + 8 dgts)
Resolution	0.01 dBm
Continuity	
Audible Indication	< 40 Ω
Diode Test	
Test Current	1.0 mA (approximate)
Open Circuit Volts	3.0 V dc typical
Peak	
AC Volts Accuracy	100 V, 750 V ranges: ± (3.0 % + 200 dgts)
	1000 mV, 10 V ranges: unspecified
AC Current	± (3.0 % + 200 dgts)
	100 µA range: unspecified
Overload Protection	
AC/DC Voltage	All ranges: 1000 V dc or 750 V ac rms
AC/DC Current	µA/mA input: F0.5 A/1000 V fast-blow ceramic (6.3 x 32 mm)
	10 A input: F10 A/1000 V fast-blow ceramic (10 x 38 mm)
	(10 A for 4 minutes maximum followed by a 12 minute cooling period)

General Specifications

Autoranging; Display: 4-3/4 digit LCD, 10,000 counts with 41-segment analog bar graph; **Display Update Rate:** 2/sec, nominal; **Power Battery:** 9 V NEDA 1604, JIS 006P, IEC 6F22; **Battery Life:** 150 hrs typical (alkaline) frequent use of backlight will decrease battery life; **Operating Temperature:** 0 °C to 45 °C at < 70 % R.H.; **Storage Temperature:** -20 °C to 60 °C, 0 to 80 % R.H. with battery removed from meter; **Temperature Coefficient:** 0.1 x (specified accuracy) per °C (0 °C to 18 °C , 28 °C to 45 °C); **Altitude:** (2000 m) 6562 ft; **Dimensions:** 7.75" x 3.55" x 2.4" (195 x 92 x 60 mm); **Weight (without holster, including battery):** 1 lb (400 gr)

Included Accessories

Test leads with threaded alligator clips (TL36), 9 V battery (installed), Magne-Grip™ Holster with magnetic hanging strap (H2-XR), spare fuse, operators manual

Features

Input lead warning; analog bar graph; Data Hold; Min/Max; Average; Relative; Peak; auto power off after 30 minutes typical; low battery indication; backlight; overrange indication; three-year warranty

Optional Accessories

VC221A Padded Vinyl Carry Case, DL248C Deluxe Test Lead Kit, DC205B Heavy Duty Case, HV231-10 High Voltage Probe, TP254 High Temperature Probe

Wavetek Meterman®
The right tool for the job.™

Wavetek Meterman Test Tools®
website: www.metermantesttools.com
email: info@metermantesttools.com

6920 Seaway Blvd.
Everett, WA 98203
fax: 425-446-4882
tel: 877-596-2680

Meterman Test Tools Europe
P.O. Box 1186
5602 BD Eindhoven
The Netherlands

©2002 Wavetek Meterman Test Tools. All rights reserved.
Printed in U.S.A. 12/2002 2062690 D-ENG-N Rev A



S J ELECTRONICS
POWER • TEST & MEASUREMENT

0800 583 44 55

Tel: +44 1536 416 200
Fax: 0800 583 55 66
sales@sjelectronics.co.uk
www.sjelectronics.co.uk