

Model CT238

Amp Clamp Accessory



CT238 Specifications (at 23 °C ± 1 °C, < 75 % R.H.)

DC Current	
Range	20 A max
Accuracy	± (1% of rdg + 2 mA)
Meter Input Impedance	10 kΩ min. and 100 pF max.
Division Ratio	10 to 1
Output	1 A DC at jaws = 100 mV DC to meter
AC Current (DC–10 kHz)	
Range	20 A rms
Accuracy	20 A (< 1 kHz): ± (1 % of rdg + 2 mA) 20 A (1 to 20 kHz): ± (3 % of rdg + 2 mA)
Meter Input Impedance	10 kΩ min. and 100 pF max.
Division Ratio	10 to 1
Output	1 A AC at jaws = 100 mV AC to meter
Overload Protection	
Overload Capacity	500 A 300 V AC on uninsulated conductors



General Specifications

Max Conductor Size: 19 mm (0.75"); Lead Length: 1.5 m (59"); Power: 9 V battery, NEDA 1604, JIS 006P, IEC 6F22; Battery Life: 30 hours (alkaline); Operating Temperature Range: - 0 °C to + 50 °C at < 80 % R.H.; Storage Temperature Range: - 20 °C to + 85 °C; Temperature Coefficient: 0.1 % of rdg per 10 °C; Dimensions: 55 x 210 x 30 mm (2.2" x 8.3" x 1.2"); Weight: 290 g (.64 lb.); Included Accessories: Operators manual

Features

Permanently Attached Leads; Zero Adjust Knob; Warranty: One-year



- AC/DC current clamp, 20 A
- Special "Low Current" version
- CAT III 300 V rated

Model CT238

Amp Clamp Accessory

Meterman.
The right tool for the job.™

Meterman Test Tools
website: www.metermantesttools.com
email: info@metermantesttools.com
6920 Seaway Blvd.
Everett, WA 98203
fax: 425-446-4882
tel: 877-596-2680

Meterman Test Tools Europe
P.O. Box 1186
5602 BD Eindhoven
The Netherlands

©2002 Meterman Test Tools. All rights reserved.
. 1/2002 1646652 D-ENG-N Rev A Pub_ID 10527-eng Rev. 1



S J ELECTRONICS
POWER • TEST & MEASUREMENT

0800 583 44 55

Tel: +44 1536 416 200

Fax: 0800 583 55 66

sales@sjelectronics.co.uk

www.sjelectronics.co.uk