

# 170 Series Digital Multimeters

Setting the new standard

True RMS



EN 61010-1  
CAT III 1000V  
CAT IV 600V

Lifetime Warranty!  
Keep your Fluke meter up and running

The three models of the new 170 Series are the new benchmarks for general purpose multimeters. They set the standard with a combination of precision, features, ease-of-use, safety and reliability.

All models offer True RMS AC voltage and current readings, 6000-count resolution, min-max-average recording, as well as frequency and capacitance ranges. Despite all these and many other useful features, the 170 Series remain easy to use. The ergonomic case with integrated holster protects the units in rough and tough environments.

To change the batteries, the case does not have to be opened as access to the batteries is through an easy-to-open battery door.

### Safety Conformance

All inputs are protected to EN61010-1 CAT IV 600V/CAT III 1000V. UL, CSA, TÜV and VDE listed.

## Features

True-RMS measurements
Digital display counts, updates 4 times per second
Display backlight
Analog bargraph / segments, updates 40 times per second
Auto and Manual ranging
Display Hold and Auto Hold
Min-Max-Average recording mode with Min/Max Alert
Temperature readings (bead thermocouple probe included)
Smoothing mode allows filtering of rapidly changing inputs
Audible continuity and diode test
Test lead alert
Unsafe voltage alert warns for voltages above 30V
Low battery indication
Ergonomic case with integrated holster
Easy battery exchange without opening the complete case
Selectable sleep mode preserves battery life

	175	177	179
AC	AC	AC	AC
6000	6000	6000	6000
Display backlight	●	●	●
33-segments	33-segments	33-segments	33-segments
Auto and Manual ranging	●	●	●
Display Hold and Auto Hold	●	●	●
Min-Max-Average recording mode with Min/Max Alert	●	●	●
Temperature readings (bead thermocouple probe included)			●
Smoothing mode allows filtering of rapidly changing inputs	●	●	●
Audible continuity and diode test	●	●	●
Test lead alert	●	●	●
Unsafe voltage alert warns for voltages above 30V	●	●	●
Low battery indication	●	●	●
Ergonomic case with integrated holster	●	●	●
Easy battery exchange without opening the complete case	●	●	●
Selectable sleep mode preserves battery life	●	●	●

LISTED



## Accessories and Ordering Information

### Included Accessories

Test leads with 4 mm lantern tips and protective cap, installed 9V battery and users manual. The 179 also includes the 80BK temperature probe.

### Ordering Information

Fluke 175 True RMS Multimeter  
Fluke 177 True RMS Multimeter  
Fluke 179 True RMS Multimeter



**S J ELECTRONICS**  
POWER • TEST & MEASUREMENT

**0800 583 44 55**

Tel: +44 1536 416 200

Fax: 0800 583 55 66

sales@sjelectronics.co.uk

www.sjelectronics.co.uk

## Specifications

Functions	Maximum	Max. resolution
Voltage DC	1000V	0.1mV
Voltage AC	1000V	0.1mV
Current DC	10A	0.01mA
Current AC	10A	0.01mA
Resistance	50MΩ	0.1Ω
Capacitance	10000µF	1nF
Frequency	100kHz	0.01Hz
Temperature	-40°C/+400°C	0.1°C

	175	177	179
±(0.15%+2)	±(0.09%+2)	±(0.09%+2)	±(0.09%+2)
±(1.0%+3)	±(1.0%+3)	±(1.0%+3)	±(1.0%+3)
±(1.0%+3)	±(1.0%+3)	±(1.0%+3)	±(1.0%+3)
±(1.5%+3)	±(1.5%+3)	±(1.5%+3)	±(1.5%+3)
±(0.9%+1)	±(0.9%+1)	±(0.9%+1)	±(0.9%+1)
±(1.2%+2)	±(1.2%+2)	±(1.2%+2)	±(1.2%+2)
±(0.1%+1)	±(0.1%+1)	±(0.1%+1)	±(0.1%+1)
			±(1.0%+10)

Accuracies are best accuracies for each function

**Battery Life** : Alkaline, 200 hrs typical

**Size (HxWxD)** : 185 mm x 90 mm x 43 mm

**Weight** : 0.42 kg

**Lifetime Warranty**