

The GPR-M Series is single output, 180W, linear DC power supply Overload and reverse polarity protection keep GPR and loads safe from unexpected conditions. High regulation and low ripple/noise are maintained at 0.01% and less than 1mVrms, respectively. Internal load selection, continuous or dynamic, accommodates certain applications such as pulsed current. The GPR-M Series is suitable for middle- to high-end bench-top application requiring preciseness.

## **GPR-M Series**



Patent No: 81011

## **FEATURES**

- \* 0.01% High Regulation
- \* Constant Voltage and Constant Current
  Operation
- \* Internal Select for Continuous or Dynamic Load
- \* Low Ripple and Noise
- \* Overload and Reverse Polarity protection
- \* 3 1/2 Digits 0.5" LED Display

SPECIFICATIONS			
CONSTANT VOLTAGE OPERATION			
Regulation Ripple & Noise	Line regulation $\le$ 0.01% + 3mV Load regulation $\le$ 0.01% + 5mV (<10A) Load regulation $\le$ 0.02% + 5mV ( $\ge$ 10A) $\le$ 1mVrms 5Hz $\sim$ 1MHz		
Recovery Time Output Range	≤100 μS( 50% Load change, Minimum load 0.5A ) 0 to rating voltage continuously adjustable		
CONSTANT CURRENT OPERATION			
Regulation	Line regulation≤0.2% + 3mA Load regulation≤0.2% + 3mA		
Ripple Current	≤3mArms		
Output Range	0 to rating amperes continuoulsy adjustable		
METER			
Digital	3 1/2 Digits 0.5" LED display		
	Accuracy $\pm$ ( 0.5% of rdg + 2 digits )		
INSULATION			
Chassis and Terminal	20M $Ω$ or above ( DC 500V )		
Chassis and AC Cord	30M $Ω$ or above ( DC 500V )		
POWER SOURCE			
AC 100V/120V/220V/240V±10%, 50/60Hz			
DIMENSIONS			
255(W) x 145(H) x 335(D) mm			

ORDERING INFORMATION				
Model	Output Volts (V)	Output Amps (A)	Weight (kg)	
GPR-1810HD 180W D.C. Power Supply	0 ~ 18	0 ~ 10	11.5	
GPR-3060D 180W D.C. Power Supply	0 ~ 30	0 ~ 6	11.5	
GPR-6030D 180W D.C. Power Supply	0 ~ 60	0 ~ 3	11.5	
ACCESSORIES: User manual x 1, Power cord x 1 Test lead GTL-105 x 1 (GPR-6030D) GTL-104 x 1 (GPR-1810DH/3060D)				
Optional Accessories				



GRA-401 Rack Adapter Panel

## S J ELECTRONICS

0800 583 44 55

Tel: +44 1536 416 200 Fax: 0800 583 55 66

sales@sjelectronics.co.uk www.sjelectronics.co.uk