

# AC Millivolt Meter



## FEATURES :

- \* 300 mV Full scale sensitivity
- \* Measures frequency from 10Hz ~ 1MHz
- \* Measures from -70dB ~ +40dB in 12 ranges
- \* Dual Channel ( GVT-427B )

GVT-427B(2CH)/GVT-417B(1CH)

## SPECIFICATIONS

<b>INPUT</b>	<b>Voltage Range</b> <b>Decibel Range</b> <b>Accuracy</b> <b>Operating Mode</b>	300 mV~100V of Full Scale in 12 ranges -70dB ~ +40dB in 12 ranges ± 3% of full scale Channel 1 and 2 separately or simultaneously at channel 1 one channel only (GVT - 417B)
	<b>Frequency Respones</b> <b>Impedance</b>	20Hz~200kHz ±3%, 10Hz~1MHz ±10% (reference 1 kHz) 1MW, approx, 40pF
<b>OUTPUT</b>	<b>Level</b> <b>Distortion</b>	Approx. 0.1Vrms at full scale Less than 2%
<b>POWER SOURCE</b>		AC 115/230V±10% , 50/60Hz
<b>ACCESSORIES</b>		Power cord x 1 Instruction Manual x 1 Test Lead GTL-101 x 2 (GTL-101 x 1 for GVT - 417B)
<b>DIMENSIONS &amp; WEIGHT</b>		130(W) x 210(H)x295(D)mm; Approx. 2.7 kg

Note : CE mark is only for GVT-417B

G4

ISO-9001 & ISO-14001



**S J ELECTRONICS**  
POWER • TEST & MEASUREMENT

**0800 583 44 55**

Tel: +44 1536 416 200

Fax: 0800 583 55 66

sales@sjelectronics.co.uk

www.sjelectronics.co.uk