

Programmable Switching D.C Power Supply

NEW



FEATURES :

- * LCD Display
- * Output ON/OFF Control
- * 3 Steps Fan Speed Control
- * OVP , OCP , OPP , OTP Protection
- * Key Lock to Avoid Error Operation
- * Normal , +% & -% Output Operation Key
- * Standard Interface : RS-232C
- * Option : Jack Type Terminal for Europe

PSP-Series

SPECIFICATIONS

OUTPUT	Model	PSP-603	PSP-405	PSP-2010	
Voltage	0 ~ 60V	0 ~ 40V	0 ~ 20V	0 ~ 10A	
Current	0 ~ 3.5A	0 ~ 5A	0 ~ 10A	0 ~ 10A	
VOLTAGE REGULATION	Load Line	≤ 10mV ≤ 0.05%	≤ 10mV ≤ 0.05%	≤ 10mV ≤ 0.05%	
CURRENT REGULATION	Load Line	≤ 5mA ≤ 0.05%	≤ 5mA ≤ 0.05%	≤ 5mA ≤ 0.05%	
RIPPLE	Voltage (mVrms) Current (mA rms)	≤ 20mV ≤ 10mA	≤ 20mV ≤ 10mA	≤ 20mV ≤ 10mA	
RESOLUTION	Voltage Current	20mV 2mA	10mV 2mA	10mV 5mA	
PROGRAM ACCURACY	Voltage Current	≤ 40V ≤ 60V ≤ 3.5A ≤ 5A ≤ 10A	± 0.05%rdg + 3digits ± 0.05%rdg + 4digits ± 0.1%rdg + 5digits ± 0.1%rdg + 5digits ± 0.3%rdg + 10digits	± 0.05%rdg + 3digits ± 0.05%rdg + 4digits ± 0.1%rdg + 5digits ± 0.1%rdg + 5digits ± 0.3%rdg + 10digits	± 0.05%rdg + 3digits ± 0.05%rdg + 4digits ± 0.1%rdg + 5digits ± 0.1%rdg + 5digits ± 0.3%rdg + 10digits
READBACK (METER) RESOLUTION	Voltage Current	As Resolution As Resolution	As Resolution As Resolution	As Resolution As Resolution	
READBACK (METER) ACCURACY	Voltage Current	As Program Accuracy As Program Accuracy	As Program Accuracy As Program Accuracy	As Program Accuracy As Program Accuracy	
PROTECTION	OVP/OCP/OPP/OTP	✓	✓	✓	
OUTPUT ON/OFF CONTROL		✓	✓	✓	
DISPLAY	LCD				
INTERFACE (STANDARD)	RS-232C				
POWER SOURCE	AC 115V/230V ± 15%, 50/60Hz				
ACCESSORIES	Power cord x 1, Instruction manual x 1, Test lead x 1				
DIMENSIONS & WEIGHT	225(W) x 100(H) x 305(D) mm ; Approx. 4kg				

D15

ISO-9001 & ISO-14001



S J ELECTRONICS
POWER • TEST & MEASUREMENT

0800 583 44 55

Tel: +44 1536 416 200

Fax: 0800 583 55 66

sales@sjelectronics.co.uk

www.sjelectronics.co.uk