



## Specification MM68 Digital Multimeter



### ELECTRICAL

All specified accuracies are at 23°C ± 5°C, <75% RH for 1 year.

**Temperature Coefficient:** 0.1 x (specified accuracy) per °C. (0°C to 18°C, 28°C to 50°C)

### DC VOLTS

**Ranges:** 220mV, 2.2V, 22V, 220V, 1000V

**Resolution:** 0.01mV, 0.0001V, 0.001V, 0.01V, 0.1 V

**Accuracy:** ± (0.05% of rdg + 5 dgts)

**Input impedance:** 220mV: >100MΩ;  
2.2V: 10 MΩ; 22V to 1000V: 9.1MΩ.

**Overload protection:** 1000V DC or 750 AC rms.

### TRUE RMS AC VOLTS

**Ranges:** 220mV, 2.2V, 22V, 220V, 750V

**Resolution:** 0.01mV, 0.0001V, 0.001V, 0.01V, 0.1V

**Accuracy:** 220mV range (50 Hz to 500 Hz) ± (1.2% of rdg + 10 dgts)

2.2V to 220V ranges (50 Hz to 500 Hz) ± (1.2% of rdg + 10 dgts)

(500 Hz to 2 kHz) ± (2.0% of rdg + 20 dgts)

750V range (50 Hz to 500 Hz) ± (2.0% of rdg + 20 dgts)

AC coupled true rms specified from 5% to 100% of range

**Crest factor:** ≤ 3

**Input impedance:** 220mV: >100MΩ; 2.2V: 10MΩ; 22V to 750V: 9.1MΩ

**Overload protection:** 1000V DC or 750 AC rms



## Specification MM68 Digital Multimeter

### DC CURRENT

**Ranges:** 220μA, 2200μA, 22mA, 220mA, 10A \*

**Resolution:** 0.01μA, 0.1μA, 0.001mA, 0.01mA, 0.001A

**Accuracy:** 220μA to 22mA ranges ± (0.5% of rdg + 10 dgts)

220mA range ± (1.0% of rdg + 10 dgts)

10A range ± (2.0% of rdg + 10 dgts)

\* Current on 10 A range applied for 60 seconds max followed by a 10 minute cooling period

**Input protection:** 0.5A/500V fast blow ceramic fuse

10A/500V fast blow ceramic fuse

### TRUE RMS AC CURRENT

**Ranges:** 220μA, 2200μA, 22mA, 220mA, 10A \*

**Resolution:** 0.01μA, 0.1μA, 0.001mA, 0.01mA, 0.001 A

**Accuracy:** 220μA to 220mA (50 Hz to 1 kHz) ± (1.5% of rdg + 5 dgts)

10A range (50 Hz to 1 kHz) ± (2.5% of rdg + 5 dgts)

\* Current on 10 A range applied for 60 seconds max followed by a 10 minute cooling period

AC coupled true rms specified from 5% to 100% of range

**Crest factor:** ≤ 3

**Input protection:** 0.5A/500V fast blow ceramic fuse

10A/500V fast blow ceramic fuse.

### RESISTANCE

**Ranges:** 220Ω, 2.2kΩ, 22kΩ, 220kΩ, 2.2MΩ, 22MΩ, 220MΩ

**Resolution:** 0.01Ω, 0.0001kΩ, 0.001kΩ, 0.01kΩ, 0.0001MΩ, 0.001MΩ, 0.1MΩ

**Accuracy:** 220Ω to 220kΩ ranges ± (0.5% of rdg + 10 dgts)

2.2MΩ range ± (1.0% of rdg + 10 dgts)

22MΩ range ± (2.0% of rdg + 10 dgts)

220MΩ range ± (5.0% of rdg + 10 dgts)



## Specification MM68 Digital Multimeter

**Open circuit voltage:** -0.45 V DC (-1.2 V DC on 220 Ω range)

**Overload protection:** 500 V DC or AC rms

### CAPACITANCE

**Ranges:** 22nF, 220nF, 2.2μF, 22μF, 220μF, 2.2mF, 22mF

**Resolution:** 0.001nF, 0.01nF, 0.0001μF, 0.001μF, 0.01μF, 0.0001mF, 0.001mF

**Accuracy:** 22nF range ± (3.0% of rdg + 80 dgts)

220nF to 220μF ranges ± (3.0% of rdg + 5 dgts)

2.2mF to 22mF range ± (5.0% of rdg + 20 dgts)

**Overload protection:** 500 V DC or AC rms

### FREQUENCY

**Ranges:** 22Hz, 220Hz, 22kHz, 220kHz, 2.2MHz, 22MHz

**Resolution:** 0.01Hz, 0.1Hz, 0.001kHz, 0.01kHz, 0.0001MHz, 0.001MHz

**Accuracy:** ± (0.1% of rdg + 3 dgts)

**Input sensitivity:** 2Hz ~ 2.2MHz: >2.5Vrms. 2.2MHz ~ 22MHz: >2.5Vrms and <5Vrms

**Minimum input:** 22Hz range > 2Hz. 220Hz range > 20Hz

**Minimum pulse width:** > 25ns

**Duty cycle limits:** > 30% and < 70%

**Overload protection:** 500VDC or AC rms

### DUTY CYCLE

**Range:** 10% to 95%

**Resolution:** 0.01%

**Pulse width:** >10us

**Frequency range:** 10% to 95% (40Hz to 20kHz)

**Accuracy:** (5V logic) ± (2.0% rdg + 5 dgts)

**Overload protection:** 500V DC or AC rms



## Specification MM68 Digital Multimeter

### CONTINUITY

**Audible indication:** < 30Ω

**Response time:** 500ms

**Overload protection:** 500V DC or AC rms

### DIODE TEST

**Test current:** 1.2mA approx

**Resolution:** 0.1mV

**Accuracy:** ± (2.0% rdg + 5 dgts)

**Audible indication:** <0.25V

**Open circuit voltage:** 3.0V DC typical

**Overload protection:** 500V DC or AC rms

### GENERAL


**Display:** 4½ digit liquid crystal display with a maximum reading of 22000.

**Analog bargraph:** 22 segments with measurement 20 times per second.

**Polarity:** Automatic, positive implied, negative polarity indication

**Overrange:** (OL) or (-OL) is displayed

**Zero:** Automatic

**Low battery indication:**  symbol is displayed when the battery voltage drops below the operating level

**Measurement rate:** 3 times per second, nominal

**Auto power off:** After approx 30 minutes

**Operating environment:** 0°C to 50°C at < 70% RH

**Storage temperature:** -20°C to 60°C at < 80% RH

**Altitude:** Up to 2000m

**Power:** Single standard 9 volt battery, NEDA 1604, JIS006P, IEC 6F22.

**Battery Life:** 150 hours typical with carbon-zinc



Specification  
MM68  
Digital Multimeter

**Dimensions:** 165mm (H) x 78mm (W) x 42.5mm (D)

**Weight:** Approx. 285g

**Includes:** TL16 test leads, Magnetic strap, 1 x spare fuse, 9V battery (installed) and instructions

**SAFETY:**

Conforms to BS EN 61010-1, CAT III 600 V, CAT II 1000V

Class II Double Insulation

Pollution Degree: 2 for indoor use

TL16 test leads conform to BS EN 61010-031, CAT III 1000V, CAT IV 600V, 10A.

**EMC:** Conforms to BS EN 61326.

**Check out what else you can get from Martindale:**

- 17th Edition Testers
- Accessories
- Calibration Equipment
- Continuity Testers
- Electricians' Kits
- Environmental Products
- Full Calibration & Repair Service
- Fuse Finders
- Digital Clamp Meters
- Digital Multimeters
- Labels
- Microwave Leakage Detectors
- Motor Maintenance Equipment
- Multifunction Testers
- Non-trip Loop Testers
- Pat Testers & Accessories
- Phase Rotation Testers
- Proving Units
- Socket Testers
- Thermometers & Probes
- Test Leads
- Voltage Indicators
- Specialist Metrohm Testers (4 & 5kV)
- Specialist Drummond Testers



**S J ELECTRONICS**  
POWER • TEST & MEASUREMENT

**0800 583 4455**  
[www.sjelectronics.co.uk](http://www.sjelectronics.co.uk)  
[sales@sjelectronics.co.uk](mailto:sales@sjelectronics.co.uk)



Martindale Electric Company Limited  
Metrohm House, Penfold Trading Estate, Imperial Way, Watford WD24 4YY, UK  
Tel: +44(0)1923 441717 Fax: +44 (0)1923 446900  
E-mail: [sales@martindale-electric.co.uk](mailto:sales@martindale-electric.co.uk)  
Website: [www.martindale-electric.co.uk](http://www.martindale-electric.co.uk)



© 2012 Martindale Electric Company Ltd.  
Registered in England No. 3387451. E. & O.E. Document Rev1 LITMM68