

AC/DC Current Measurement Systems

TCPA300, TCP312A, TCP305A, TCP303, TCPA400, TCP404XL Datasheet



The TCP300 and TCP400 Series AC/DC current measurement family is a highly advanced current measurement system for today's current measurement needs. When connected to Tektronix oscilloscopes with TEKPROBE Level II, TekConnect (w/ TCA-BNC), or TekVPI (w/ TPA-BNC) interfaces, current measurements and calculations are simple and easy.

Key performance specifications

- DC - 100 MHz, Current Probe Amplifier (TCPA300) uses:
 - DC - 100 MHz, 30 A DC (TCP312A)
 - DC - 50 MHz, 50 A DC (TCP305A)
 - DC - 15 MHz, 150 A DC (TCP303)
 - DC - 50 MHz, Current Probe Amplifier (TCPA400) Uses:
 - DC - 2 MHz, 750 A DC¹ (TCP404XL) (500 A DC Continuous)
- ¹Derated with duty cycle

Key features

- Automatic scaling and units² - Oscilloscope on-screen readout of magnitude and amps reduces measurement errors with no more hand calculations
- AC/DC input coupling
- Low insertion impedance reduces device under test loading
- Split-core construction allows easy circuit connection
- Status indicators provide visual operating status and notification of potential error conditions - degauss, probe open, overload, not terminated into 50 Ω , noncompatible probe type

- Low DC drift and noise allows improved low-level current measurements
- 3rd party safety certification

² Requires a TDS TEKSCOPE oscilloscope or a TekConnect oscilloscope with TCA-BNC adapter

Applications

- Development and analysis solutions for designers, installers, and service personnel in telecom, data comm, computer, and semiconductor power electronics environments for:
 - Power supplies (switching and linear)
 - Semiconductor devices (SCRs, IGBTs, MOSFETs, CMOS, BJTs)
 - Power inverters/converters
 - Electronic ballasts
 - Industrial/consumer electronics
 - Mobile communications (phone, satellite, relay stations)
 - Motor drives
- Transportation systems (electronic vehicles, electric trains, locomotives, avionics)

Meets today's AC/DC current measurement applications

The TCPA300 amplifier, when used with TCP312A, TCP305A, or TCP303 probes, provides a wide range of current measurement capability and spans the gap between low-level milliamp measurements to very high current levels. These three probes provide current measurement capabilities of 30 A, 50 A, and 150 A DC continuous. For even higher current levels, the TCPA400 amplifier with the TCP404XL current probe measures 500 A DC continuous and 750 A DC continuous, derated with duty cycle.

Higher-frequency performance is available with the TCP312A w/TCPA300 providing ≥ 100 MHz bandwidth and a maximum current of 30 A DC.

Measurement errors and manual calculations are now a thing of the past

With this new series of current measurement tools, automatic control and on-screen scaling and units is provided for users of Tektronix TDS3000, TDS500, TDS600, TDS700, TDS5000, TDS6000, and TDS7000B series oscilloscope systems (the DPO3000, MDO/MSO/DPO4000, MSO/DPO5000, and DPO7000 series oscilloscopes, the TPA-BNC adapter is required).

The TCP300/TCP400 current measurement systems seamlessly integrate with your TDS series oscilloscope.

Even non-TEKPROBE systems can use the TCPA300/400 series to make proper current measurements by simply multiplying the measured output voltage on the oscilloscope by the TCPA300/400 series range setting.

Specifications

All specifications apply to all models unless noted otherwise.

Model overview

	TCP312A w/ TCPA300	TCP305A w/ TCPA300	TCP303 w/ TCPA300	TCP404XL w/ TCPA400
Bandwidth	DC – 100 MHz	DC – 50 MHz	DC – 15 MHz	DC – 2 MHz
Rise time	≤3.5 ns	≤7 ns	≤23 ns	≤175 ns
DC accuracy	±3% of reading	±3% of reading	±3% of reading	±3% of reading
DC accuracy, typical	±1% of reading	±1% of reading	±1% of reading	±1% of reading
Lowest measurable current (at ±3% accuracy at DC) Scope set to 1 mV/div and 20 MHz BW limited	1 mA	5 mA	5 mA	1 A
Maximum Amp-Second product, typical (Based on amplifier range setting)	50 A*μS – 1 A/V 500 A*μS – 10 A/V	500 A*μS – 5 A/V NA – 10 A/V	3,000 A*μS – 5 A/V 15,000 A*μS – 50 A/V	NA – 1 A/mV
Maximum wire voltage, bare insulated	150 V CAT II 300 V CAT II	150 V CAT II 300 V CAT II	600 V CAT I & II 300 V CAT III	600 V CAT I & II 300 V CAT III
AC-coupling low-frequency Bandwidth, typical (Low pass – 3 dB point)	<7 Hz	<7 Hz	<7 Hz	<7 Hz
Displayed RMS noise, typical (at 20 MHz bandwidth limit)	≤250 μA _{RMS}	≤1.25 mA _{RMS}	≤2.5 mA _{RMS}	≤250 mA _{RMS}
Signal delay (to output BNC)	17 ns	19 ns	40 ns	80 ns
Insertion impedance	0.11 Ω at 1 MHz 0.12 Ω at 10 MHz 0.35 Ω at 50 MHz 0.7 Ω at 100 MHz	0.02 Ω at 1 MHz 0.1 Ω at 10 MHz 0.35 Ω at 50 MHz	0.01 Ω at 1 MHz 0.025 Ω at 5 MHz 0.1 Ω at 15 MHz	0.1 m Ω at 10 kHz 0.6 m Ω at 100 kHz 8 m Ω at 1 MHz 16 m Ω at 2 MHz

Characteristics

Maximum current ratings

High-current sensitivity

	TCP312A w/ TCPA300	TCP305A w/ TCPA300	TCP303 w/ TCPA300	TCP404XL w/ TCPA400
Range	10 A/V	10 A/V	50 A/V	1 A/mV
DC (continuous)	30 A	50 A	150 A	500 A (750 A)
RMS (sinusoidal)	21.2 A	35.4 A	150 A	500 A
Peak	50 A	50 A	500 A	750 A

Low-current sensitivity

Range	1 A/V	5 A/V	5 A/V	N/A
DC (continuous)	5 A	25 A	25 A	N/A
RMS (sinusoidal)	3.5 A	17.7 A	17.7 A	N/A
Peak	50 A	50 A	500 A	N/A

Physical characteristics

Amplifiers

TCPA300/TCPA400	
Length	17.3 cm (6.8 in)
Width	16.7 cm (6.6 in)
Height	9.14 cm (3.6 in)
Weight	1.14 kg (2.5 lb)

Probes

	TCP305A/TCP312A	TCP303	TCP404XL
Length	20 cm (7.77 in)	26.8 cm (10.55 in)	26.8 cm (10.55 in)
Width	6 cm (0.625 in)	4.1 cm (1.60 in)	4.1 cm (1.60 in)
Height	3.2 cm (1.25 in)	15.6 cm (6.13 in)	15.6 cm (6.13 in)
Weight	0.15 kg (0.33 lb)	0.66 kg (1.45 lb)	0.88 kg (1.90 lb)

Maximum conductor size

TCP312A	TCP305A	TCP303	TCP404XL
5.0 mm (0.15 in)	5.0 mm (0.15 in)	21 mm x 25 mm (0.83 x 1.0 in)	21 mm x 25 mm (0.83 x 1.0 in)

Cable length

1.5 m (60 in)	1.5 m (60 in)	2 m (78.7 in)	8 m (315 in)
---------------	---------------	---------------	--------------

EMC environment and safety

Safety compliance

	TCP312A/305A probe and amplifier	Amplifiers	TCP303/404XL probe and amplifier
U.S. NRTL listing	UL61010-2-032, UL61010-1	UL3111-1, first edition	UL3111-2-032, UL3111-2-031; UL3111-1
Canadian certification	CAN/CSA C22.2 No. 61010-1, CAN/CSA C22.2 No. 61010-2-032	CAN/CSA C22.2 No.1010.1-92	CAN/CSA C22.2 No.1010.1-92
European Union compliance	EN61010-1, EN61010-2-032	EN61010-1:2001	EN61010-1/A2, EN61010-2-031, EN61010-2-032
Other			IEC61010-2-032

Electromagnetic compatibility, amplifiers only

EC Council Directive 89/336/EEC, FCC Part 15, Subpart B Class A, AS/NZS 2064.1/2.

Temperature

Operating

0 °C to +50 °C (32 °F to 122 °F)

Nonoperating

-40 °C to +75 °C (-40 °F to 167 °F)

Datasheet

Humidity

Operating	5% to 95% R.H. to +30 °C (86 °F) 5% to 85% R.H. +30 °C to +50 °C (86 °F to 122 °F)
Nonoperating	5% to 95% R.H. to +30 °C (86 °F) 5% to 85% R.H. +30 °C to +75 °C (86 °F to 167 °F)

Altitude

Operating	2000 m (6800 ft.) maximum
Nonoperating	12,192 m (40,000 ft.) maximum

Ordering information

Models

Probes

TCP312A Probe	AC/DC current, DC to 100 MHz; 30 A DC (Requires TCPA300 amplifier)
TCP305A Probe	AC/DC current, DC to 50 MHz; 50 A DC (Requires TCPA300 amplifier)
TCP303 Probe	AC/DC current, DC to 15 MHz; 150 A DC (Requires TCPA300 amplifier)
TCP404XL Probe	AC/DC current, DC to 2 MHz; 500 A DC (750 A DC derated with duty cycle) (Requires TCPA400 amplifier)

Amplifiers

TCPA300 Amplifier	AC/DC current probe, DC to 100 MHz, (Requires TCP305A or TCP312A or TCP303 probes)
TCPA400 Amplifier	AC/DC current probe, DC to 50 MHz, (Requires TCP404XL probe)

Recommended accessories

Cover, large probe protective; (for TCP303, TCP404XL)	016-1924-00
Case, transit; current measurement systems	016-1922-00
50 Ω feedthrough termination	011-0049-02
50 Ω BNC-to-BNC coaxial cable	012-0117-00
TEKPROBE interface cable, TCPA300 or TCPA400 amplifier to TDS series oscilloscopes	012-1605-00
Current loop, 1 turn, 50 Ω, BNC connector (for TCP305A, TCP312A, TCP202A)	067-2396-00
Current loop, 1 turn, 50 Ω, BNC connector (for TCP303, TCP404XL)	015-0601-50
TCPA300/TCPA400 amplifier calibration adapter	174-4765-00
Power measurements deskew fixture for TCP202A, TCP305A, TCP312A, TCP303 probes	067-1478-00

Warranty

One year parts and labor.

Power requirements

Amplifiers	90 V to 264 V, 47 to 440 Hz, 50 W; Maximum CAT II (auto switch)
Probes	TCP312A, TCP305A, TCP303 probes require a TCPA300 Amplifier; TCP404XL probe requires a TCPA400 Amplifier

Options

Power plug options

Opt. A0	North America power plug (115 V, 60 Hz)
Opt. A1	Universal Euro power plug (220 V, 50 Hz)
Opt. A2	United Kingdom power plug (240 V, 50 Hz)
Opt. A3	Australia power plug (240 V, 50 Hz)
Opt. A5	Switzerland power plug (220 V, 50 Hz)
Opt. A6	Japan power plug (100 V, 110/120 V, 60 Hz)
Opt. A10	China power plug (50 Hz)
Opt. A11	India power plug (50 Hz)
Opt. A12	Brazil power plug (60 Hz)
Opt. A99	No power cord

ServiceOptions

Opt. C3	Calibration Service 3 Years
Opt. C5	Calibration Service 5 Years
Opt. D1	Calibration Data Report
Opt. D3	Calibration Data Report 3 Years (with Opt. C3)
Opt. D5	Calibration Data Report 5 Years (with Opt. C5)
Opt. R3	Repair Service 3 Years (including warranty)
Opt. R3DW	Repair Service Coverage 3 Years (includes product warranty period). 3-year period starts at time of instrument purchase
Opt. R5	Repair Service 5 Years (including warranty)
Opt. R5DW	Repair Service Coverage 5 Years (includes product warranty period). 5-year period starts at time of instrument purchase
Opt. SILV400	Standard warranty extended to 5 years (TCP305A, TCP312A, TCPA300, TCPA400)
Opt. SILV600	Standard warranty extended to 5 years (TCP303, TCP404XL)



Tektronix is registered to ISO 9001 and ISO 14001 by SRI Quality System Registrar.

ASEAN / Australasia (65) 6356 3900
Belgium 00800 2255 4835*
Central East Europe and the Baltics +41 52 675 3777
Finland +41 52 675 3777
Hong Kong 400 820 5835
Japan 81 (3) 6714 3010
Middle East, Asia, and North Africa +41 52 675 3777
People's Republic of China 400 820 5835
Republic of Korea 001 800 8255 2835
Spain 00800 2255 4835*
Taiwan 886 (2) 2722 9622

Austria 00800 2255 4835*
Brazil +55 (11) 3759 7627
Central Europe & Greece +41 52 675 3777
France 00800 2255 4835*
India 000 800 650 1835
Luxembourg +41 52 675 3777
The Netherlands 00800 2255 4835*
Poland +41 52 675 3777
Russia & CIS +7 (495) 6647564
Sweden 00800 2255 4835*
United Kingdom & Ireland 00800 2255 4835*

Balkans, Israel, South Africa and other ISE Countries +41 52 675 3777
Canada 1 800 833 9200
Denmark +45 80 88 1401
Germany 00800 2255 4835*
Italy 00800 2255 4835*
Mexico, Central/South America & Caribbean 52 (55) 56 04 50 90
Norway 800 16098
Portugal 80 08 12370
South Africa +41 52 675 3777
Switzerland 00800 2255 4835*
USA 1 800 833 9200

* European toll-free number. If not accessible, call: +41 52 675 3777

Updated 10 April 2013

For Further Information. Tektronix maintains a comprehensive, constantly expanding collection of application notes, technical briefs and other resources to help engineers working on the cutting edge of technology. Please visit www.tektronix.com.

Copyright © Tektronix, Inc. All rights reserved. Tektronix products are covered by U.S. and foreign patents, issued and pending. Information in this publication supersedes that in all previously published material. Specification and price change privileges reserved. TEKTRONIX and TEK are registered trademarks of Tektronix, Inc. All other trade names referenced are the service marks, trademarks, or registered trademarks of their respective companies.



24 Apr 2013

60W-16458-7

www.tektronix.com



 **S J ELECTRONICS**
POWER • TEST & MEASUREMENT

0800 583 4455
www.sjelectronics.co.uk
sales@sjelectronics.co.uk