

We measure it.



# Wood/material moisture measuring instrument

## testo 606 - Pocket-sized material moisture measurement

---

Precise measurement of wood moisture

---

Further characteristics curves for locating wet spots in building materials

---

Hold-function for convenient read-out of measurement values

---

Display illumination

---

Additional advantages of testo 606-2:

---

Measurement of temperature and humidity in ambient air

---

Incl. dewpoint calculation and Wet Bulb.

---



Illustration 1:1

The testo 606-1/-2 is a particularly convenient and easy-to-operate pocket-sized material moisture measuring instrument. The material moisture is directly displayed in percentage by weight via stored material characteristic curves. For the measurement of wood moisture, characteristic curves are available for beech, spruce, larch, oak, pine and maple. In order to locate wet spots in building materials, curves are additionally stored for cement screed, plaster, anhydrite screed, cement mortar, lime mortar, and brick.

The testo 606-2 measures air humidity and temperature in addition to material moisture. This enables drying conditions to be determined quickly and reliably on site, for example. The clip-on protective cap, wrist strap and a belt holder allow the safe storage of the testo 606-1/-2

[www.testo.co.uk](http://www.testo.co.uk)

## Technical data / Accessories

### testo 606-1

testo 606-1; wood and material moisture meter, incl. protective cap, batteries and calibration protocol



Part no. 0560 6060

#### General technical data

Oper. temp.	-10 to +50 °C
Storage temp.	-40 to +70 °C
Dimensions	119 x 46 x 25 mm (incl. protective cap)
Battery type	2 batteries Type AAA
Measuring rate	1 s
Weight	90 g (protective cap and batteries included)
Protection class	IP20

### testo 606-2

testo 606-2; wood and material moisture meter with built-in moisture measurement and NTC air thermometer, incl. protective cap, batteries and calibration protocol



Part no. 0560 6062

Technical data	testo 606-1/-2	testo 606-2	
Sensor types	Material moisture (based on conductivity)	NTC	Testo humid. sensor, cap.
Meas. range	0 to 50 %	-10 to +50 °C	0 to 100 %RH
Accuracy ±1 digit	±1 %	±0.5 °C	±2.5 %RH (5 to 95 %RH)
Resolution	0.1	0.1 °C	0.1 %RH
Battery life	200 h (average, without display illumination)	130 h (average, without display illumination)	

Accessories	Part no.
<b>Accessories for measuring instrument</b>	
For testo 606-1: Spare electrodes (1 pair)	0192 5358
For testo 606-2: Spare electrodes (1 pair)	0192 5348
ISO calibration certificate humidity; Calibration points 11.3 %RH and 75.3 %RH at +25°C	0520 0006
ISO calibration certificate/temperature; temp. data logger; calibration points -8°C; 0°C; +40°C per channel/instrument	0520 0171

[www.testo.co.uk](http://www.testo.co.uk)



**S J ELECTRONICS**  
POWER • TEST & MEASUREMENT

**0800 583 4455**  
[www.sjelectronics.co.uk](http://www.sjelectronics.co.uk)  
[sales@sjelectronics.co.uk](mailto:sales@sjelectronics.co.uk)